

## **TYRES**

Product group	Tyres	
Item number	10000337	
Valid tyre size	290 / 90 - 20	
LI / SI / PR	168 A2 / 152 B, 18 PR	
TL/TT	тт	
SET	Tube + Flap	
Brand	ВКТ	
Tread pattern	EM 933 SUPER	





## Notes and features

- The BKT EM 933 Super is a tyre for excavators in use for excavation or loading work.
- Its special sidewall with protruding rib allows close contact between the tyres during twin use and prevents stones from penetrating.
- An intermediate rubber ring between the two tyres is therefore no longer necessary.
- The special tread pattern provides excellent traction even in the most difficult conditions.
- The tyre also guarantees very good ride comfort and improved self-cleaning properties.



## **Technical Informations**

Item number	10000337
EAN	8903094070183
Valid tyre size	290 / 90 - 20
LI / SI / PR	168 A2 / 152 B, 18 PR
TL/TT	тт
SET	Tube + Flap
Ventilposition	central
Brand	BKT
Tread pattern	EM 933 SUPER
TRA Code	E2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	67.07
Recommended rim size	8.0
Maximum air pressure [bar].	9,00
Section width (mm)	295
Outer diameter of tyre [mm].	1055
Tread depth (mm)	22,5
Number of lugs	22x2
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A2	5600	10		9,00	
152 B	3550	50		9,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.