Bohnenkamp Moving Professionals

RIMS

Product group	Rims
Item number	10000934
Valid rim size	DW 13 L x 24
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-55
Rim colour	Black
Brand	Jantsa





Technical Informations Load capacity of rim 1 [kg] 4750 Speed Rims 1 [km/h] 40 Maximum speed [km/h]. 40 Type of drive Driven axle Nettogewicht [kg] (gültig) 53,50 Hump kein Hump Valve protection VSH Single / multi-part einteilig **Rim material** steel RAL RAL9005 **Cavity Sealed** No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Disc thickness [mm]	12
Knurling	with knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	8
Bolt hole design EUWA	B22 ES 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No

14.03.2025