

WHEELS

Product group	Wheels
Item number	10000964
Valid wheel size	400 / 70 R 24
Brand	BKT
Tread pattern	Multimax MP 527
Valid rim size	DW 13 L x 24
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-55
Rim colour	Black
Load capacity complete wheel [kg]	3550
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	140,65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Bohnenkamp
Moving Professionals

BKT
GROWING TOGETHER

Technical Informations

Assembly Item no. Tyres	• 15735243
LI / SI / PR	152 A8 / 152 B
Load capacity 1 [kg]	3550
Speed 1 [km/h].	40
Load capacity 2 [kg]	3550
Speed 2 [km/h].	50
Maximum air pressure [bar].	4,00
TL/TT	TL

Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	404
Stat. radius (SLR) [mm]	542
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3597
Tread depth (mm)	28,5
Number of lugs	27x2
Assembly Item no. Rim	• 10000934
Load capacity of rim 1 [kg]	4750
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Driven axle
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27.0
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9005
Valve seat	External Valve
Disc thickness [mm]	12.0

Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Knurling	with knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade