

TYRES

| Product group | Tyres |
|-----------------|----------------|
| Item number | 10001029 |
| Valid tyre size | 480 / 70 R 28 |
| LI / SI / PR | 148 A8 / 145 D |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM700 |





Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.



Technical Informations

| Item number | 10001029 |
|------------------------------|----------------|
| EAN | 8059971003239 |
| Valid tyre size | 480 / 70 R 28 |
| LI / SI / PR | 148 A8 / 145 D |
| TL/TT | TL |
| Brand | Trelleborg |
| Tread pattern | TM700 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 112,00 |
| Recommended rim size | 15 |
| Permitted rim size | 14, 16 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 468 |
| Outer diameter of tyre [mm]. | 1415 |
| Stat. radius (SLR) [mm] | 636 |
| Rolling circumference [mm]. | 4240 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 148 A8 | 3150 | 40 | | 2,40 | |
| 145 D | 2900 | 65 | | 2,40 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.