

TYRES

Product group	Tyres
Item number	10001049
Valid tyre size	380 / 85 R 28
LI / SI / PR	133 A8 / 130 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600



Notes and features

- Protects turf and crops due to innovative tread pattern.
- High load capacity.

- Low soil compaction.
- Optimal traction.



Technical Informations

Item number	10001049
EAN	8059971004632
Valid tyre size	380 / 85 R 28
Alternative size 1	14.9R28
LI / SI / PR	133 A8 / 130 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM600
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	79,00
Recommended rim size	13
Permitted rim size	12, 11
Maximum air pressure [bar].	1,60
Section width (mm)	390
Outer diameter of tyre [mm].	1357
Stat. radius (SLR) [mm]	615
Rolling circumference [mm].	4085
Tread depth (mm)	45,0
Number of lugs	19x2
Lug width (mm)	41
Tyre capacity 75% [ltr.]	239
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		1,60	
130 B	1900	50		1,60	