

TYRES

Product group	Tyres
Item number	10001053
Valid tyre size	480 / 70 R 24
LI / SI / PR	138 A8 / 138 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700



Bohnenkamp
Moving Professionals



Notes and features

- The TM 700 is an agricultural radial tyre.
- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.
- Top-level driving performance.

Technical Informations

Item number	10001053
EAN	8059971001952
Valid tyre size	480 / 70 R 24
LI / SI / PR	138 A8 / 138 B
TL/TT	TL
Brand	Trelleborg
Tread pattern	TM700
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	89,88
Recommended rim size	15
Permitted rim size	16, 14
Maximum air pressure [bar].	1,60
Section width (mm)	468
Outer diameter of tyre [mm].	1300
Stat. radius (SLR) [mm]	580
Rolling circumference [mm].	3875
Tread depth (mm)	47,0
Lug width (mm)	46
Tyre capacity 75% [litr.]	293
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
138 A8	2360	40		1,60	
138 B	2360	50		1,60	