# Bohnenkamp
**Moving Professionals**

## TYRES

| | |
|---|---|
| **Product group** | Tyres |
| **Item number** | 10001054 |
| **Valid tyre size** | 420 / 70 R 24 |
| **LI / SI / PR** | 130 A8 / 130 B |
| **TL/TT** | TL |
| **Brand** | Trelleborg |
| **Tread pattern** | TM700 |



**TRELLEBORG**

## Notes and features

- The TM 700 is an agricultural radial tyre.

- It provides excellent traction in the field and maximum self-cleaning properties, comfort and very good handling on the road.

- Top-level driving performance.

## Technical Informations

| | |
|---|---|
| **Item number** | 10001054 |
| **EAN** | 8059971001914 |
| **Valid tyre size** | 420 / 70 R 24 |
| **LI / SI / PR** | 130 A8 / 130 B |
| **TL/TT** | TL |
| **Brand** | Trelleborg |
| **Tread pattern** | TM700 |
| **Antistatic** | No |
| **Tyre colour** | Black |
| **ECE regulation number** | not necessary |
| **Nettogewicht [kg] (gültig)** | 73,50 |
| **Recommended rim size** | 13 |
| **Permitted rim size** | 12, 14 |
| **Maximum air pressure [bar].** | 1,60 |
| **Section width (mm)** | 415 |
| **Outer diameter of tyre [mm].** | 1253 |
| **Stat. radius (SLR) [mm]** | 562 |
| **Rolling circumference [mm].** | 3705 |
| **Tread depth (mm)** | 45,0 |
| **Number of lugs** | 17x2 |
| **Lug width (mm)** | 46 |
| **Tyre capacity 75% [ltr.]** | 229 |
| **E-Ready** | No |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 130 A8 | 1900 | 40 | | 1,60 | |
| 130 B | 1900 | 50 | | 1,60 | |