

TYRES

Product group	Tyres
Item number	10001258
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	135 / 133 K
TL/TT	TL
Brand	Semperit
Tread pattern	Runner T3



Bohnenkamp
■ ■ ● Moving Professionals

SEMPERIT 
Seit 1906.

Notes and features

- The Semperit Runner T3 is a truck trailer tyre for local and long-distance traffic.
- Its particularly wide tread and the cut-resistant rubber compound ensure slow wear and a long service life.
- Over its entire service life, the tyre offers very good wet grip.
- Thanks to its sipes, the tyre offers excellent performance all year round, even in winter road conditions.

Technical Informations

Item number	10001258
EAN	4024067004043
Valid tyre size	215 / 75 R 17.5
LI / SI / PR	135 / 133 K
TL/TT	TL
Brand	Semperit
Tread pattern	Runner T3
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	D
Wet grip	C
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	27,70
Recommended rim size	6.00
Maximum air pressure [bar].	8,50
Section width (mm)	217
Tread width (mm)	178
Outer diameter of tyre [mm].	775
Stat. radius (SLR) [mm]	360
Rolling circumference [mm].	2375
Tread depth (mm)	11,4

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 K	2180	110	Single	8,50	
133 K	2060	110	Twin	8,50	
				8,50	