

## TYRES

Product group	Tyres
Item number	10001262
Valid tyre size	710 / 35 R 22.5
LI / SI / PR	157 D
TL/TT	TL
Brand	Alliance
Tread pattern	882



## Notes and features

- Newly-developed flotation tyre with steel belt reinforcement.
- Primary use on heavy transport vehicles and slurry tankers as well as manure spreaders with mixed road and field use.
- Directional block tread pattern for low rolling resistance and very good self-cleaning.
- High air volume for low soil compaction and high load-bearing capacity even with low inflation pressure.
- Steel belt offers additional protection against punctures.

## Technical Informations

Item number	10001262
EAN	8903635050964
Valid tyre size	710 / 35 R 22.5
LI / SI / PR	157 D
TL/TT	TL
Brand	Alliance
Tread pattern	882
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	106,00
Recommended rim size	AG24.00
Maximum air pressure [bar].	4,00
Section width (mm)	712
Outer diameter of tyre [mm].	1069
Stat. radius (SLR) [mm]	481
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3263
Contact area [cm²]	1512.1
Tread depth (mm)	22,0
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 D	4125	65		4,00	