

## **TYRES**

| Product group   | Tyres               |  |
|-----------------|---------------------|--|
| Item number     | 10001305            |  |
| Valid tyre size | 320 / 65 R 18       |  |
| LI / SI / PR    | 109 A8 / 109 B      |  |
| TL/TT           | TL                  |  |
| Brand           | ВКТ                 |  |
| Tread pattern   | Agrimax Turf RT 333 |  |



## Notes and features

- The BKT Agrimax Turf RT 333 is a radial tyre for small tractors in gardening, wine or fruit cultivation.
- Its rounded tyre shoulder ensures low soil compaction and prevents damage to delicate soils.
- Thanks to the special directional block tread and the high tread pattern depth, the tyre provides good traction in the field and on the road and a long service life.
- Furthermore, the tyre has excellent self-cleaning properties.



## **Technical Informations**

| Item number                  | 10001305            |
|------------------------------|---------------------|
| item number                  |                     |
| EAN                          | 8903094071081       |
| Valid tyre size              | 320 / 65 R 18       |
| LI / SI / PR                 | 109 A8 / 109 B      |
| TL/TT                        | TL                  |
| Brand                        | ВКТ                 |
| Tread pattern                | Agrimax Turf RT 333 |
| Antistatic                   | No                  |
| Tyre colour                  | Black               |
| ECE regulation number        | ECE 106             |
| Nettogewicht [kg] (gültig)   | 34,82               |
| Recommended rim size         | W10                 |
| Permitted rim size           | W9, W11             |
| Maximum air pressure [bar].  | 1,60                |
| Section width (mm)           | 319                 |
| Outer diameter of tyre [mm]. | 873                 |
| Stat. radius (SLR) [mm]      | 394                 |
| Speed Radius Index (SRI)     | 425                 |
| Rolling circumference [mm].  | 2591                |
| Tread depth (mm)             | 24,5                |
| E-Ready                      | No                  |

## **Load capacity**

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 109 A8 | 1030               | 40           |               | 1,60                        |              |
| 109 B  | 1030               | 50           |               | 1,60                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.