

## **TYRES**

Product group	Tyres
Item number	10001706
Valid tyre size	600 / 60 R 30.5
LI / SI / PR	179 D
TL/TT	TL
Brand	ВКТ
Tread pattern	FL 695





## Notes and features

- The BKT FL 695 is a flotation radial tyre for trailers in construction and transport use.
- The special tread pattern with tread blocks arranged in the centre of the tread guarantees very good selfcleaning.
- The strong carcass allows for excellent stability and high load capacities under all ground conditions.
- Steel inserts protect the tyre from damage.



## **Technical Informations**

Item number	10001706
EAN	8903094073832
Valid tyre size	600 / 60 R 30.5
LI / SI / PR	179 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 695
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	224,91
Recommended rim size	AG20.00
Maximum air pressure [bar].	6,00
Section width (mm)	611
Outer diameter of tyre [mm].	1495
Stat. radius (SLR) [mm]	693
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4586
Tread depth (mm)	26,5
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.