

TYRES

Product group	Tyres	
Item number	10001723	
Valid tyre size	710 / 40 R 22.5	
LI / SI / PR	165 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	885	



Notes and features

- The Alliance 885 was developed for balers, grain wagons, cultivators, small agricultural trailers and similar towed vehicles.
- The rounded tyre shoulder and large contact area protect crops and soil from damage.
- The large lugs in the middle of the tread provide comfortable handling during transport journeys.
- Its low rolling resistance reduces fuel consumption.
- Thanks to the reinforced sidewall and the strong casing with steel belts, the tyre is optimally protected against damages.



Technical Informations

Item number	10001723
EAN	8903635053156
Valid tyre size	710 / 40 R 22.5
LI / SI / PR	165 D
TL/TT	TL
Brand	Alliance
Tread pattern	885
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	124,80
Recommended rim size	AG24.00
Maximum air pressure [bar].	5,00
Section width (mm)	726
Outer diameter of tyre [mm].	1140
Stat. radius (SLR) [mm]	512
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3471
Contact area [cm²]	1763.60
Tread depth (mm)	24,0
Number of lugs	21x2
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		5,00	