

TYRES

Product group	Tyres	
Item number	10001892	
Valid tyre size	650 / 85 R 38	
LI / SI / PR	173 D / 169 E	
TL/TT	TL	
Brand	Michelin	
Tread pattern	MachXBib	





Notes and features

- Super-wide tyre for upper performance class.
- Specially designed for gentle soil tillage.

• Suitable for heavy road transport.



Technical Informations

Item number	10001892
EAN	3528706566400
Valid tyre size	650 / 85 R 38
LI / SI / PR	173 D / 169 E
TL/TT	TL
Brand	Michelin
Tread pattern	MachXBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	354,00
Recommended rim size	DW23B(A)
Permitted rim size	DW20B(A), MW23B(A)
Maximum air pressure [bar].	2,40
Section width (mm)	674
Outer diameter of tyre [mm].	2075
Stat. radius (SLR) [mm]	952
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6169
Contact area [cm²]	3544
Tread depth (mm)	68,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	856.50
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		2,40	
169 E	5800	70		2,40	