

TYRES

Product group	Tyres
Item number	10001896
Valid tyre size	320 / 85 R 28
LI / SI / PR	124 A8 / 124 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II



Notes and features

- The Traxion 85 II is a standard radial tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs provides good traction and self-cleaning.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life

Technical Informations

Item number	10001896
EAN	8714692344725
Valid tyre size	320 / 85 R 28
Alternative size 1	12.4R28
LI / SI / PR	124 A8 / 124 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	59,34
Recommended rim size	W11
Permitted rim size	W9, (D)W10
Maximum air pressure [bar].	1,60
Section width (mm)	330
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	575
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3700
Tread depth (mm)	41,0
Tyre capacity 75% [ltr.]	115
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 A8	1600	40		1,60	
124 B	1600	50		1,60	