

WHEELS

| | |
|-----------------------------------|--------------------|
| Product group | Wheels |
| Item number | 10001927 |
| Valid wheel size | 560 / 45 R 22.5 |
| Brand | BKT |
| Tread pattern | FL 630 Ultra |
| Valid rim size | AG 16.00 x 22.5 H2 |
| Rim connection | 10/281/335 |
| Bolt hole design | A3 |
| Offset (mm) | +50 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 4875 |
| Speed complete wheel [km/h] | 40 |
| Nettogewicht [kg] (gültig) | 140,71 |
| RDA (Reifendruckregelanlage) | No |
| RDKS (Reifendruckkontrollsystem) | No |



Technical Informations

| | |
|-----------------------------|----------------|
| Assembly Item no. Tyres | • 15715113 |
| LI / SI / PR | 163 A8 / 152 D |
| Load capacity 1 [kg] | 4875 |
| Speed 1 [km/h]. | 40 |
| Load capacity 2 [kg] | 3550 |
| Speed 2 [km/h]. | 65 |
| Maximum air pressure [bar]. | 4,00 |
| TL/TT | TL |

| | |
|--------------------------------|------------|
| Tyre colour | Black |
| E-Ready | No |
| Antistatic | No |
| ECE regulation number | ECE 106 |
| Section width (mm) | 543 |
| Stat. radius (SLR) [mm] | 490 |
| Speed Radius Index (SRI) | 525 |
| Rolling circumference [mm]. | 3290 |
| Tread depth (mm) | 28,5 |
| Number of lugs | 18x2 |
| Tyre capacity 75% [ltr.] | 247 |
| Assembly Item no. Rim | • 10001602 |
| Load capacity of rim 1 [kg] | 7250 |
| Speed Rims 1 [km/h] | 40 |
| Load capacity of rim 2 [kg] | 5300 |
| Speed Rims 2 [km/h] | 65 |
| Maximum speed [km/h]. | 65 |
| Type of drive | Towed axle |
| Number of bolt holes | 10 |
| hub hole diameter [mm]. | 281 |
| Bolt hole circle diameter [mm] | 335 |
| Bolt hole diameter [mm] | 27.0 |
| Bolt hole design EUWA | B22 ES 36 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| Rim centering | BC |
| Rim material | steel |

| | |
|--------------------------|------------------|
| RAL | RAL9006 |
| Valve seat | External Valve |
| Disc thickness [mm] | 12.0 |
| Ventilation holes | No |
| Single / multi-part | einteilig |
| Hump | H2 |
| Valve protection | VSH |
| Cavity Sealed | No |
| Knurling | without knurling |
| Verschweißung beidseitig | No |
| Assembly Item no. Valve | • 47201039 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |
| Valve hole diameter [mm] | 15.7 |
| Valve design | Rubber valve |
| Valve length [mm] | 55.0 |
| Valve angle [°] | gerade |