

TYRES

Product group	Tyres	
Item number	10001952	
Valid tyre size	600 / 50 R 22.5	
LI / SI / PR	163 D	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	ENDURION TRAILER	



Notes and features

- The Vredestein Endurion Trailer is a tyre for heavy agricultural trailers.
- Its directional tread pattern ensures continuous ground contact.
- This results in particularly high driving comfort and a long service life.
- The arrangement of the tread blocks guarantees very good self-cleaning.
- The steel belted carcass, a circumferential stabilizing ring in the tread and the integrated sidewall protection provide additional stability.



Technical Informations

Item number	10001952
EAN	8714692805530
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	163 D
TL/TT	TL
Brand	Vredestein
Tread pattern	ENDURION TRAILER
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	130,00
Recommended rim size	AG 20.00
Maximum air pressure [bar].	5,00
Section width (mm)	605
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	535
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3575
Tread depth (mm)	24,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 D	4875	65		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.