

WHEELS

Product group	Wheels
Item number	10002042
Valid wheel size	500 / 50 - 17
Brand	Starco
Tread pattern	SG Flotation
Valid rim size	16.00 x 17
Rim connection	8/221/275
Bolt hole design	B2
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	3875
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	84,75
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19811107
LI / SI / PR	155 A8 / 142 A8, 18 PR
Load capacity 1 [kg]	3875
Speed 1 [km/h].	40
Load capacity 2 [kg]	2650
Speed 2 [km/h].	40
Maximum air pressure [bar].	3,70
TL/TT	TL

Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	503
Stat. radius (SLR) [mm]	411
Rolling circumference [mm].	2842
Tread depth (mm)	20,0
Assembly Item no. Rim	• 30810344
Load capacity of rim 1 [kg]	4000
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2900
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 DS 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	9

Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade