

TYRES

Product group	Tyres
Item number	10002107
Valid tyre size	455 / 45 R 22.5
LI / SI / PR	160 J
TL/TT	TL
Brand	Bohnenkamp
Tread pattern	Agrarmax MZL



Notes and features

- The Agrarmax MZL is a retreaded tyre on premium casing for use on agricultural trailers.
- The tyre offers a high load capacity up to 90 or 100 km/h depending on the size.
- Its tread pattern offers very good driving characteristics on the road and good self-cleaning properties.
- Its wide contact area and block tread pattern ensure even ground pressure distribution and soil protection during field operations.

Technical Informations

Item number	10002107
EAN	4040658117251
Valid tyre size	455 / 45 R 22.5
LI / SI / PR	160 J
TL/TT	TL
Brand	Bohnenkamp
Tread pattern	Agrarmax MZL
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 109
Nettogewicht [kg] (gültig)	66,00
Recommended rim size	15.00
Permitted rim size	14.00
Maximum air pressure [bar].	9,00
Section width (mm)	470
Outer diameter of tyre [mm].	1002
Stat. radius (SLR) [mm]	463
Rolling circumference [mm].	3005
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 J	4500	100		9,00	
	5000	65		9,00	
	5450	40		9,00	
	6000	25		9,00	