

## RIMS

Product group	Rims
Item number	10002546
Valid rim size	8.25 x 16.5
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+40
Rim colour	Silver
Brand	Jantasa



## Technical Informations

Load capacity of rim 1 [kg]	2850
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2400
Speed Rims 2 [km/h]	40
Load capacity of rim 3 [kg]	3200
Speed Rims 3 [km/h]	15
Load capacity of rim 4 [kg]	2650
Speed of wheels 4 [km/h].	30
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	15,80

Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	8
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 DS 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Geeignet für RDA	No