

RIMS

Product group	Rims
Item number	10002619
Valid rim size	7.00 I x 12
Rim connection	5/67/112
Bolt hole design	E1
Rim colour	Silver
Brand	Fira



Technical Informations

Load capacity of rim 1 [kg]	1200
Speed Rims 1 [km/h]	40
Axle position agriculture 1	Free Rolling
Load capacity of rim 2 [kg]	1080
Speed Rims 2 [km/h]	40
Axle position agriculture 2	Drive Wheel
Load capacity of rim 3 [kg]	944
Speed Rims 3 [km/h]	60
Axle position agriculture 3	Free Rolling
Load capacity of rim 4 [kg]	1056
Speed of wheels 4 [km/h].	60

Axle position agriculture 4	Drive Wheel
Maximum speed [km/h].	60
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	7,23
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	5
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Number of bolt holes	5
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No
Geeignet für RDA	No