

WHEELS

Product group	Wheels
Item number	10002648
Valid wheel size	385 / 65 R 22.5
Brand	Bohnenkamp
Tread pattern	Boka Agrar Trans II
Valid rim size	11.75 x 22.5
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	80
Nettogewicht [kg] (gültig)	128.95
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19968044
LI / SI / PR	160 F
Load capacity 1 [kg]	4500
Speed 1 [km/h].	80
Maximum air pressure [bar].	8,50
TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No

ECE regulation number	not necessary
Type of retreading	Hot retreaded ECO
Section width (mm)	379
Stat. radius (SLR) [mm]	496
Assembly Item no. Rim	• 33060275
Load capacity of rim 1 [kg]	6250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5200
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	80
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 ES 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No

Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade