

## WHEELS

Product group	Wheels
Item number	10002655
Valid wheel size	330 / 40 B 12
Brand	Carlisle
Tread pattern	Ultra Trac
Valid rim size	10.50 I x 12 H2
Rim connection	5/66.6/112
Bolt hole design	E1
Rim colour	Silver
Load capacity complete wheel [kg]	800
Speed complete wheel [km/h]	20
Nettogewicht [kg] (gültig)	22,82
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 12500595
LI / SI / PR	100 A4, 4 PR
Load capacity 1 [kg]	800
Speed 1 [km/h].	20
Maximum air pressure [bar].	1,24
TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No

ECE regulation number	ECE 106
Section width (mm)	328
Stat. radius (SLR) [mm]	259
Rolling circumference [mm].	1725
Tread depth (mm)	7,1
Assembly Item no. Rim	• 31610062
Load capacity of rim 1 [kg]	1100
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	1000
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	20
Number of bolt holes	5
hub hole diameter [mm].	66.6
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	H2
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No

Assembly Item no. Valve	• 47200650
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	11.3
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade