

WHEELS

Product group	Wheels
Item number	10002663
Valid wheel size	385 / 65 R 22.5
Brand	Bohnenkamp
Tread pattern	RE Power WP Truck
Valid rim size	11.75 x 22.5 H
Rim connection	10/281/335
Bolt hole design	B33
Rim colour	Silver
Load capacity complete wheel [kg]	4500
Speed complete wheel [km/h]	110
Nettogewicht [kg] (gültig)	112,28
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 19968076
LI / SI / PR	160 K
Load capacity 1 [kg]	4500
Speed 1 [km/h].	110
Maximum air pressure [bar].	9,00
TL/TT	TL
M+S	M+S
3PMSF	3PMSF
Tyre colour	Black

E-Ready	No
Antistatic	No
ECE regulation number	ECE 109
Type of retreading	Hot retreaded ECO
Section width (mm)	385
Tread depth (mm)	16,0
Assembly Item no. Rim	• 10000369
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	110
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	26.0
Bolt hole design EUWA	M22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BHC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	11
Ventilation holes	Yes
Single / multi-part	einteilig
Hump	H
Cavity Sealed	No

Verschweißung beidseitig	No
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	9.7