

## **TYRES**

| Product group   | Tyres         |  |
|-----------------|---------------|--|
| Item number     | 10002708      |  |
| Valid tyre size | 650 / 60 R 34 |  |
| LI / SI / PR    | 159 D / 155 E |  |
| TL/TT           | TL            |  |
| Brand           | Michelin      |  |
| Tread pattern   | RoadBib       |  |





## Notes and features

- The Michelin Roadbib is a radial tractor tyre for use in the field and on the road, with at least 80% on roads.
- Its large contact area ensures even ground pressure distribution, low rolling resistance and consequently low fuel consumption.
- The special tread pattern with the continuous central bar enables a high level of running smoothness and very good ride comfort when driving on the road.



## **Technical Informations**

| Item number                  | 10002708           |
|------------------------------|--------------------|
| EAN                          | 3528705562496      |
| Valid tyre size              | 650 / 60 R 34      |
| LI / SI / PR                 | 159 D / 155 E      |
| TL/TT                        | TL                 |
| Brand                        | Michelin           |
| Tread pattern                | RoadBib            |
| Antistatic                   | No                 |
| Tyre colour                  | Black              |
| Nettogewicht [kg] (gültig)   | 230,00             |
| Recommended rim size         | DW20B(A)           |
| Permitted rim size           | DW21B(A), DW23B(A) |
| Maximum air pressure [bar].  | 2,40               |
| Section width (mm)           | 667                |
| Outer diameter of tyre [mm]. | 1651               |
| Stat. radius (SLR) [mm]      | 762                |
| Rolling circumference [mm].  | 4935               |
| Tread depth (mm)             | 38,0               |
| Number of lugs               | 20x2               |
| Tyre capacity 75% [ltr.]     | 500                |
| E-Ready                      | No                 |

## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 159 D | 4375               | 65           |               | 2,40                        |              |
| 155 E | 3875               | 70           |               | 2,40                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.