

TYRES

| | |
|-----------------|------------------|
| Product group | Tyres |
| Item number | 10002712 |
| Valid tyre size | VF 710 / 70 R 42 |
| LI / SI / PR | 179 D / 175 E |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | EvoBib |



Notes and features

- The Michelin Evobib is an innovative tyre for field and road applications.
- The special 2-in-1-technology enables the tyre to change its tread pattern and contact area according to the inflation pressure.
- It combines the characteristics of 2 tyres and adapts perfectly to the respective operating and soil conditions.
- Used in the field with an inflation pressure of less than 1.2 bar, the tyre shoulders drop.
- This increases the contact area by up to 20%, traction is improved and the soil is optimally protected.
- When used on the road with higher inflation pressure, the tyre shoulders are raised, only the middle part of the tread touches the ground.
- This reduces rolling resistance and fuel consumption and increases the ride comfort.

Technical Informations

| | |
|------------------------------|--------------------|
| Item number | 10002712 |
| EAN | 3528707075109 |
| Valid tyre size | VF 710 / 70 R 42 |
| LI / SI / PR | 179 D / 175 E |
| TL/TT | TL |
| Brand | Michelin |
| Tread pattern | EvoBib |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 350,00 |
| Recommended rim size | DW25B(A) |
| Permitted rim size | DW23B(A), MW25B(A) |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 716 |
| Outer diameter of tyre [mm]. | 2063 |
| Stat. radius (SLR) [mm] | 887 |
| Rolling circumference [mm]. | 6069 |
| Tread depth (mm) | 54,0 |
| Number of lugs | 28x2 |
| Tyre capacity 75% [ltr.] | 867 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 179 D | 7750 | 65 | | 2,40 | |
| 175 E | 6900 | 70 | | 2,40 | |