

TYRES

Product group	Tyres
Item number	10002713
Valid tyre size	VF 650 / 65 R 34
LI / SI / PR	167 D / 163 E
TL/TT	TL
Brand	Michelin
Tread pattern	EvoBib



Notes and features

- The Michelin Evobib is an innovative tyre for field and road applications.
- The special 2-in-1-technology enables the tyre to change its tread pattern and contact area according to the inflation pressure.
- It combines the characteristics of 2 tyres and adapts perfectly to the respective operating and soil conditions.
- Used in the field with an inflation pressure of less than 1.2 bar, the tyre shoulders drop.
- This increases the contact area by up to 20%, traction is improved and the soil is optimally protected.
- When used on the road with higher inflation pressure, the tyre shoulders are raised, only the middle part of the tread touches the ground.
- This reduces rolling resistance and fuel consumption and increases the ride comfort.

Technical Informations

Item number	10002713
EAN	3528706674617
Valid tyre size	VF 650 / 65 R 34
LI / SI / PR	167 D / 163 E
TL/TT	TL
Brand	Michelin
Tread pattern	EvoBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	241,00
Recommended rim size	DW23B(A)
Permitted rim size	DW21B(A)
Maximum air pressure [bar].	2,40
Section width (mm)	679
Outer diameter of tyre [mm].	1707
Stat. radius (SLR) [mm]	745
Rolling circumference [mm].	5032
Tread depth (mm)	55,0
Number of lugs	23x2
Tyre capacity 75% [ltr.]	600
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 D	5450	65		2,40	
163 E	4875	70		2,40	