

TYRES

Product group	Tyres
Item number	10002714
Valid tyre size	VF 650 / 60 R 34
LI / SI / PR	165 D / 161 E
TL/TT	TL
Brand	Michelin
Tread pattern	EvoBib



Notes and features

- The Michelin Evobib is an innovative tyre for field and road applications.
- The special 2-in-1-technology enables the tyre to change its tread pattern and contact area according to the inflation pressure.
- It combines the characteristics of 2 tyres and adapts perfectly to the respective operating and soil conditions.
- Used in the field with an inflation pressure of less than 1.2 bar, the tyre shoulders drop.
- This increases the contact area by up to 20%, traction is improved and the soil is optimally protected.
- When used on the road with higher inflation pressure, the tyre shoulders are raised, only the middle part of the tread touches the ground.
- This reduces rolling resistance and fuel consumption and increases the ride comfort.

Technical Informations

Item number	10002714
EAN	3528707856159
Valid tyre size	VF 650 / 60 R 34
LI / SI / PR	165 D / 161 E
TL/TT	TL
Brand	Michelin
Tread pattern	EvoBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	240,00
Recommended rim size	DW23B(A)
Permitted rim size	DW24B(A)
Maximum air pressure [bar].	2,40
Section width (mm)	677
Outer diameter of tyre [mm].	1646
Stat. radius (SLR) [mm]	705
Rolling circumference [mm].	4841
Tread depth (mm)	55,0
Tyre capacity 75% [litr.]	500
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		2,40	
161 E	4625	70		2,40	