

TYRES

Product group	Tyres	
Item number	10002719	
Valid tyre size	440 / 80 R 34	
LI / SI / PR	159 A8 / 155 D	
TL/TT	TL	
Brand	Michelin	
Tread pattern	CrossGrip	





Notes and features

- The Michelin CrossGrip is a versatile municipal tyre for all-season use on roads, grass and snow.
- The tyre provides high loading capacities at speeds up to 65 km/h.
- Its special tread pattern design enables very good traction, even in wintry weather conditions.
- The tyre features excellent steering characteristics, also in reverse.



Technical Informations

Item number	10002719
EAN	3528709675284
Valid tyre size	440 / 80 R 34
LI / SI / PR	159 A8 / 155 D
TL/TT	TL
Brand	Michelin
Tread pattern	CrossGrip
M+S	M+S
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	130,00
Recommended rim size	DW14L
Permitted rim size	DW15L, DW16L
Maximum air pressure [bar].	3,20
Section width (mm)	431
Outer diameter of tyre [mm].	1580
Stat. radius (SLR) [mm]	718
Speed Radius Index (SRI)	750
Rolling circumference [mm].	4706
Contact area [cm²]	2133
Tread depth (mm)	30,0
Number of lugs	42x2
Tyre capacity 75% [ltr.]	295.50
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		3,20	
155 D	3875	65		3,20	