

TYRES

Product group	Tyres
Item number	10002732
Valid tyre size	VF 480 / 80 R 42 CFO
LI / SI / PR	176 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo



Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

Technical Informations

Item number	10002732
EAN	8903094075317
Valid tyre size	VF 480 / 80 R 42 CFO
LI / SI / PR	176 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	203,53
Recommended rim size	DW16L
Permitted rim size	DW15L
Maximum air pressure [bar].	3,60
Section width (mm)	479
Tread width (mm)	450
Outer diameter of tyre [mm].	1835
Stat. radius (SLR) [mm]	838
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5572
Tread depth (mm)	43,0
Number of lugs	28x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 D	7100	65		3,60	