

WHEELS

Product group	Wheels
Item number	10002738
Valid wheel size	10.0 / 75 - 15.3
Brand	BKT
Tread pattern	AW 702
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	E2
Offset (mm)	-5
Rim colour	Silver
Load capacity complete wheel [kg]	1550
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	29,95
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711730
LI / SI / PR	123 A8, 10 PR
Load capacity 1 [kg]	1550
Speed 1 [km/h].	40
Maximum air pressure [bar].	3,90
TL/TT	TL
Tyre colour	Black
E-Ready	No

Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	274
Stat. radius (SLR) [mm]	351
Rolling circumference [mm].	2213
Tread depth (mm)	10,5
Assembly Item no. Rim	• 31810196
Load capacity of rim 1 [kg]	3150
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2650
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH

Cavity Sealed	No
Verschweißung beidseitig	No
Number of drain holes	2
Assembly Item no. Valve	• 47200570
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade