

## WHEELS

|                                   |                  |
|-----------------------------------|------------------|
| Product group                     | Wheels           |
| Item number                       | 10002739         |
| Valid wheel size                  | 10.0 / 75 - 15.3 |
| Brand                             | BKT              |
| Tread pattern                     | AS 504           |
| Valid rim size                    | 9.00 x 15.3      |
| Rim connection                    | 6/161/205        |
| Bolt hole design                  | E2               |
| Offset (mm)                       | -5               |
| Rim colour                        | Silver           |
| Load capacity complete wheel [kg] | 1550             |
| Speed complete wheel [km/h]       | 40               |
| Nettogewicht [kg] (gültig)        | 34,52            |
| RDA (Reifendruckregelanlage)      | No               |
| RDKS (Reifendruckkontrollsystem)  | No               |



## Technical Informations

|                             |                        |
|-----------------------------|------------------------|
| Assembly Item no. Tyres     | • 15711750             |
| LI / SI / PR                | 111 A8 / 123 A8, 10 PR |
| Load capacity 1 [kg]        | 1090                   |
| Speed 1 [km/h].             | 40                     |
| Load capacity 2 [kg]        | 1550                   |
| Speed 2 [km/h].             | 40                     |
| Maximum air pressure [bar]. | 3,90                   |
| TL/TT                       | TL                     |

|                                |                |
|--------------------------------|----------------|
| Tyre colour                    | Black          |
| E-Ready                        | No             |
| Antistatic                     | No             |
| ECE regulation number          | ECE 106        |
| Section width (mm)             | 264            |
| Stat. radius (SLR) [mm]        | 360            |
| Speed Radius Index (SRI)       | 360            |
| Rolling circumference [mm].    | 2404           |
| Tread depth (mm)               | 23,0           |
| Tyre capacity 75% [ltr.]       | 45.93          |
| Assembly Item no. Rim          | • 31810196     |
| Load capacity of rim 1 [kg]    | 3150           |
| Speed Rims 1 [km/h]            | 25             |
| Load capacity of rim 2 [kg]    | 2650           |
| Speed Rims 2 [km/h]            | 40             |
| Maximum speed [km/h].          | 40             |
| Type of drive                  | Towed axle     |
| Number of bolt holes           | 6              |
| hub hole diameter [mm].        | 161            |
| Bolt hole circle diameter [mm] | 205            |
| Bolt hole diameter [mm]        | 21.5           |
| Countersinking                 | Sphere         |
| Spherical countersink [mm].    | R16            |
| Rim centering                  | BC             |
| Rim material                   | steel          |
| RAL                            | RAL9006        |
| Valve seat                     | External Valve |

|                          |              |
|--------------------------|--------------|
| Ventilation holes        | No           |
| Single / multi-part      | einteilig    |
| Hump                     | kein Hump    |
| Valve protection         | VSH          |
| Cavity Sealed            | No           |
| Verschweißung beidseitig | No           |
| Number of drain holes    | 2            |
| Assembly Item no. Valve  | • 47200570   |
| Preassembled valve       | No           |
| TPMS-kompatibles Ventil  | No           |
| Valve hole diameter [mm] | 15.7         |
| Valve design             | Rubber valve |
| Valve designation ETRTO  | V2.03.3      |
| Valve length [mm]        | 43.0         |
| Valve angle [°]          | gerade       |