

WHEELS

Product group	Wheels
Item number	10002740
Valid wheel size	400 / 60 - 15.5
Brand	BKT
Tread pattern	AW 708
Valid rim size	13.00 x 15.5
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-15
Rim colour	Silver
Load capacity complete wheel [kg]	3250
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	58,76
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711822
LI / SI / PR	149 A8, 18 PR
Load capacity 1 [kg]	3250
Speed 1 [km/h].	40
Maximum air pressure [bar].	4,50
TL/TT	TL
Tyre colour	Black
E-Ready	No

Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	405
Stat. radius (SLR) [mm]	380
Rolling circumference [mm].	2564
Tread depth (mm)	12,0
Assembly Item no. Rim	• 10000755
Load capacity of rim 1 [kg]	4500
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3750
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 ES 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	10
Ventilation holes	No
Single / multi-part	einteilig

Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade