

WHEELS

Product group	Wheels
Item number	10002743
Valid wheel size	11.5 / 80 - 15.3
Brand	BKT
Tread pattern	AS 504
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	+40
Rim colour	Silver
Load capacity complete wheel [kg]	2430
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	44,59
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711784
LI / SI / PR	126 A8 / 139 A8, 14 PR
Load capacity 1 [kg]	1700
Speed 1 [km/h].	40
Load capacity 2 [kg]	2430
Speed 2 [km/h].	40
Maximum air pressure [bar].	4,80
TL/TT	TL

Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	290
Stat. radius (SLR) [mm]	380
Speed Radius Index (SRI)	410
Rolling circumference [mm].	2540
Assembly Item no. Rim	• 10002843
Load capacity of rim 1 [kg]	3450
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2900
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 DS 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	8

Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade