

WHEELS

Product group	Wheels
Item number	10002748
Valid wheel size	23 x 8.50 - 12
Brand	BKT
Tread pattern	Skid Power HD
Valid rim size	7.00 I x 12
Rim connection	5/67/112
Bolt hole design	E1
Rim colour	Silver
Load capacity complete wheel [kg]	545
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	19,35
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15772041
LI / SI / PR	87 A8, 6 PR
Load capacity 1 [kg]	545
Speed 1 [km/h].	40
Maximum air pressure [bar].	3,40
TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No

Direction	Right
ECE regulation number	ECE 106
Section width (mm)	215
Stat. radius (SLR) [mm]	271
Rolling circumference [mm].	1764
Tread depth (mm)	14,5
Assembly Item no. Rim	• 10002619
Load capacity of rim 1 [kg]	1200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	1080
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	5
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	5
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No

Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47200650
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	11.3
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade