

## **WHEELS**

Product group	Wheels
Item number	10002749
Valid wheel size	23 x 8.50 - 12
Brand	вкт
Tread pattern	Skid Power HD
Valid rim size	7.00 l x 12
Rim connection	5/67/112
Bolt hole design	E1
Rim colour	Silver
Load capacity complete wheel [kg]	545
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	19,35
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## **Technical Informations**

Assembly Item no. Tyres	15772041
LI / SI / PR	87 A8, 6 PR
Load capacity 1 [kg]	545
Speed 1 [km/h].	40
Maximum air pressure [bar].	3,40
TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Direction	Left
ECE regulation number	ECE 106
Section width (mm)	215
Stat. radius (SLR) [mm]	271
Rolling circumference [mm].	1764
Tread depth (mm)	14,5
Assembly Item no. Rim •	10002619
Load capacity of rim 1 [kg]	1200
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	1080
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	5
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	5
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	47200650
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	11.3
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade