

RIMS

Product group	Rims
Item number	10002759
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	M22
Offset (mm)	+120
Rim colour	Black
Brand	Jamak



Technical Informations

Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	48,10
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005
Cavity Sealed	No

Disc thickness [mm]	13
Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	HB
Number of bolt holes	10
Bolt hole design EUWA	M22
Bolt hole diameter [mm]	26
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation	58 MS
Valve designation ETRTO	V3.22.1
Valve length [mm]	58.0
Valve angle [°]	45
Geeignet für RDA	No