

RIMS

Product group	Rims
Item number	10002760
Valid rim size	9.00 x 22.5
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+161
Half centre distance (HMA) [mm]	175.5
Rim colour	Black
Brand	Jamak



Technical Informations

Load capacity of rim 1 [kg]	6000
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	4000
Speed Rims 2 [km/h]	100
Load capacity of rim 3 [kg]	6700
Speed Rims 3 [km/h]	25
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	50.3
Hump	kein Hump

Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005
Cavity Sealed	No
Disc thickness [mm]	14.5
Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Geeignet für RDA	No