

WHEELS

Product group	Wheels
Item number	10002777
Valid wheel size	215 / 75 - 17.5
Brand	BKT
Tread pattern	Rib Master
Valid rim size	6.75 x 17.5
Rim connection	8/221/275
Bolt hole design	M22
Offset (mm)	+130
Rim colour	Silver
Load capacity complete wheel [kg]	2650
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	44,39
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15712440
LI / SI / PR	142 A8, 16 PR
Load capacity 1 [kg]	2650
Speed 1 [km/h].	40
Maximum air pressure [bar].	9,00
TL/TT	TL
Tyre colour	Black
E-Ready	No

Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	220
Stat. radius (SLR) [mm]	360
Rolling circumference [mm].	2310
Tread depth (mm)	11,0
Assembly Item no. Rim	• 33060069
Load capacity of rim 1 [kg]	2750
Speed Rims 1 [km/h]	100
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	26
Bolt hole design EUWA	M22
Rim centering	HB
Rim material	steel
RAL	RAL9006
Valve seat	Internal Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201034
Preassembled valve	No

TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve length [mm]	54.0
Valve angle [°]	36