

## WHEELS

Product group	Wheels
Item number	10002852
Valid wheel size	355 / 65 - 16
Brand	Deli
Tread pattern	SG-316
Valid rim size	11 x 16
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2650
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	49,61
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 19111135
LI / SI / PR	142 A8, 14 PR
Load capacity 1 [kg]	2650
Speed 1 [km/h].	40
Maximum air pressure [bar].	4,00
TL/TT	TL
Tyre colour	Black
E-Ready	No
Antistatic	No

ECE regulation number	ECE 106
Section width (mm)	353
Stat. radius (SLR) [mm]	386
Rolling circumference [mm].	2631
Tread depth (mm)	10,0
Assembly Item no. Rim	• 30012030
Load capacity of rim 1 [kg]	3550
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	1600
Speed Rims 2 [km/h]	80
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 ES 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No

---

Verschweißung beidseitig	No
Assembly Item no. Valve	• 47200571
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7