

WHEELS

Product group	Wheels
Item number	10002854
Valid wheel size	14.9 - 24
Brand	Alliance
Tread pattern	329
Valid rim size	W 12 x 24
Rim connection	16/220.7/260
Offset (mm)	-73
Rim colour	Grey
Load capacity complete wheel [kg]	1800
Speed complete wheel [km/h]	12
Nettogewicht [kg] (gültig)	111,95
RDA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 10002680
LI / SI / PR	128 A8, 8 PR
Load capacity 1 [kg]	1800
Speed 1 [km/h].	40
Maximum air pressure [bar].	2,10
TL/TT	TL
Tyre colour	Black
E-Ready	No
TRA Code	R3

Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	394
Stat. radius (SLR) [mm]	574
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3700
Tread depth (mm)	21,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	138.75
Assembly Item no. Rim	• 10002773
Load capacity of rim 1 [kg]	3000
Speed Rims 1 [km/h]	12
Maximum speed [km/h].	12
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	16
hub hole diameter [mm].	220.7
Bolt hole circle diameter [mm]	260
Bolt hole diameter [mm]	17.5
Rim centering	HB
Rim material	steel
RAL	RAL7024
Valve seat	External Valve
Disc thickness [mm]	15
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH

Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade