Bohnenkamp Moving Professionals

19.05.2025

TYRES

Product group	Tyres	
Item number	10002856	
Valid tyre size	VF 750 / 45 R 26.5	
LI / SI / PR	176 D	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	FLOTATION OPTIMALL	



Notes and features

- The Vredestein Flotation Optimall is a flotation radial tyre with VF technology for agricultural trailers.
- Its flat tread pattern with rounded tyre shoulders protects the ground, especially when turning at the edge of the field.
- The arrangement of the tread blocks ensures very good self-cleaning.
- Transverse lugs and the spacing between the lugs ensure excellent lateral grip and stable handling on slopes.
- The tread enables continuous contact with the ground and thus offers good ride comfort and a long service life.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10002856
EAN	8714692805578
Valid tyre size	VF 750 / 45 R 26.5
LI / SI / PR	176 D
TL/TT	TL
Brand	Vredestein
Tread pattern	FLOTATION OPTIMALL
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	180,00
Recommended rim size	AG 24.00
Maximum air pressure [bar].	4,00
Section width (mm)	750
Outer diameter of tyre [mm].	1355
Stat. radius (SLR) [mm]	595
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4090
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	389
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 D	7100	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.