

TYRES

Product group	Tyres
Item number	10002857
Valid tyre size	VF 710 / 45 R 22.5
LI / SI / PR	170 D
TL/TT	TL
Brand	Vredestein
Tread pattern	FLOTATION OPTIMALL



Notes and features

- The Vredestein Flotation Optimall is a flotation radial tyre with VF technology for agricultural trailers.
- Its flat tread pattern with rounded tyre shoulders protects the ground, especially when turning at the edge of the field.
- The arrangement of the tread blocks ensures very good self-cleaning.
- Transverse lugs and the spacing between the lugs ensure excellent lateral grip and stable handling on slopes.
- The tread enables continuous contact with the ground and thus offers good ride comfort and a long service life.

Technical Informations

Item number	10002857
EAN	8714692805561
Valid tyre size	VF 710 / 45 R 22.5
LI / SI / PR	170 D
TL/TT	TL
Brand	Vredestein
Tread pattern	FLOTATION OPTIMALL
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	160,00
Recommended rim size	AG24.00
Maximum air pressure [bar].	4,00
Section width (mm)	710
Outer diameter of tyre [mm].	1210
Stat. radius (SLR) [mm]	530
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3655
Tread depth (mm)	23,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 D	6000	65		4,00	