

TYRES

Product group	Tyres
Item number	10002901
Valid tyre size	6.00 R 9
LI / SI / PR	121 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 63



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Liftmax LM 63 is an industrial tyre for transport work in industrial applications.
- Its tread pattern with 3 circumferential tread ribs ensures low rolling resistance, good wet grip and even wear.
- The all-steel carcass with multi-layer steel belts guarantees exceptional stability and prevents vibrations.

Technical Informations

Item number	10002901
EAN	8903094063901
Valid tyre size	6.00 R 9
LI / SI / PR	121 A5
TL/TT	TL
Brand	BKT
Tread pattern	Liftmax LM 63
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	13,29
Recommended rim size	4.00E
Maximum air pressure [bar].	10,00
Section width (mm)	160
Outer diameter of tyre [mm].	542
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
121 A5	1450	25		10,00	