Bohnenkamp 📕 🛑 Moving Professionals

TYRES

Product group	Tyres	
Item number	10002935	
Valid tyre size	VF 1050 / 50 R 32 CFO	
LI / SI / PR	198 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 377 +	





Notes and features

- The Alliance Agriflex 377+ is a VF tyre for manure . spreaders, sprayers, harvesting vehicles and grain carts.
- The new tread ensures a maximum contact area for low • soil compaction and optimum traction.
- The rounded tyre shoulder protects the ground and prevents tyre damage caused by stubble.
- VF technology enables up to 40% higher load capacity at • the same air pressure compared to standard tyres.
- The steel belted carcass and a strong wear-resistant • rubber compound ensure stability and durability.
- The robust rubber compound effectively protects the tyre from damage (Stubble Guard) and ensures a long service life.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10002935
EAN	7291050085243
Valid tyre size	VF 1050 / 50 R 32 CFO
LI / SI / PR	198 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 377 +
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	424,00
Recommended rim size	36VA
Maximum air pressure [bar].	3,60
Section width (mm)	1059
Outer diameter of tyre [mm].	1863
Stat. radius (SLR) [mm]	821
Speed Radius Index (SRI)	675
Rolling circumference [mm].	5650
Contact area [cm²]	5622
Tread depth (mm)	46,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	1248.75
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
198 D	13200	65		3,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.