

TYRES

Product group	Tyres
Item number	10002969
Valid tyre size	650 / 65 R 30.5
LI / SI / PR	176 D
TL/TT	TL
Brand	ВКТ
Tread pattern	Ridemax FL 693 M





Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.



Technical Informations

Item number	10002969
EAN	8903094075324
Valid tyre size	650 / 65 R 30.5
LI / SI / PR	176 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	197,47
Recommended rim size	AG20.00
Maximum air pressure [bar].	4,00
Section width (mm)	645
Outer diameter of tyre [mm].	1623
Stat. radius (SLR) [mm]	734
Rolling circumference [mm].	4939
Tread depth (mm)	24,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 D	7100	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.