

## TYRES

Product group	Tyres
Item number	10002996
Valid tyre size	VF 320 / 90 R 54 CFO
LI / SI / PR	168 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Spargo



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors.
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases.
- Excellent ride comfort and high machine stability.

**Technical Informations**

<b>Item number</b>	10002996
<b>EAN</b>	8903094075249
<b>Valid tyre size</b>	VF 320 / 90 R 54 CFO
<b>LI / SI / PR</b>	168 D
<b>TL/TT</b>	TL
<b>Brand</b>	BKT
<b>Tread pattern</b>	Agrimax Spargo
<b>TRA Code</b>	R1
<b>Antistatic</b>	No
<b>Tyre colour</b>	Black
<b>ECE regulation number</b>	ECE 106
<b>Nettogewicht [kg] (gültig)</b>	143,04
<b>Recommended rim size</b>	W11
<b>Permitted rim size</b>	W10, DW10, W10L, DW11
<b>Maximum air pressure [bar].</b>	4,40
<b>Section width (mm)</b>	323
<b>Tread width (mm)</b>	275
<b>Outer diameter of tyre [mm].</b>	1948
<b>Stat. radius (SLR) [mm]</b>	910
<b>Speed Radius Index (SRI)</b>	925
<b>Rolling circumference [mm].</b>	5946
<b>Tread depth (mm)</b>	34,5
<b>Number of lugs</b>	40x2
<b>E-Ready</b>	Yes

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 D	5600	65		4,40	