

## **TYRES**

Product group	Tyres	
Item number	10003132	
Valid tyre size	VF 680 / 80 R 38 CFO  188 D  TL  Alliance	
LI / SI / PR		
TL/TT		
Brand		
Tread pattern	Agriflex 372 +	





## Notes and features

- The Alliance 372+ is a VF tyre for high performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.



## **Technical Informations**

Item number	10003132	
EAN	8903635053323	
Valid tyre size	VF 680 / 80 R 38 CFO	
LI / SI / PR	188 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Agriflex 372 +	
Carcass properties	Steel Belted	
Antistatic	No	
Tyre colour	Black	
ECE regulation number	ECE 106	
Nettogewicht [kg] (gültig)	307,20	
Recommended rim size	DW23B	
Permitted rim size	DW21B, DW24B	
Maximum air pressure [bar].	2,80	
Section width (mm)	687	
Outer diameter of tyre [mm].	2053	
Stat. radius (SLR) [mm]	898	
Speed Radius Index (SRI)	975	
Rolling circumference [mm].	6058	
Contact area [cm²]	4424.7	
Tread depth (mm)	58,0	
Number of lugs	23x2	
Tyre capacity 75% [ltr.]	879	
Guarantee period	10 years	
E-Ready	No	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
188 D	10000	65		2,80	