

TYRES

Product group	Tyres
Item number	10003133
Valid tyre size	500 / 50 - 22.5
LI / SI / PR	151 A8 / 163 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	328 Value Plus



Notes and features

- Flotation tyre with traction pattern for light conditions, e.g. on towed and mounted equipment as well as agricultural trailers, presses etc.
- Very good self-cleaning properties and simultaneous soil protection due to traction tread pattern.
- Rounded shoulders additionally protect green areas and plant stock.
- Not suitable for heavy vehicles and/or long road journeys under high loads.

Technical Informations

Item number	10003133
EAN	8903635065586
Valid tyre size	500 / 50 - 22.5
LI / SI / PR	151 A8 / 163 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	328 Value Plus
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	62,50
Recommended rim size	AG16.00
Maximum air pressure [bar].	4,00
Section width (mm)	503
Outer diameter of tyre [mm].	1085
Stat. radius (SLR) [mm]	488
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3291
Contact area [cm²]	1402.2
Tread depth (mm)	22,0
Number of lugs	26x2
Tyre capacity 75% [ltr.]	168.30
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 A8	3450	40	Drive Wheel	4,00	
163 A8	4875	40	Free Rolling	4,00	