

TYRES

Product group	Tyres
Item number	10003223
Valid tyre size	405 / 70 R 18
LI / SI / PR	153 A2 / 146 J
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 525



Notes and features

- The BKT Multimax MP 525 is an MPT radial tyre for telehandlers, skid steer loaders and graders in agro-industrial use.
- Its all-steel carcass allows high load capacities and higher speeds on and off the road.
- The non-directional tread provides outstanding traction and self-cleaning properties.
- The strong side wall provides exceptional stability when lifting.
- The cut- and puncture-resistant rubber compound protects against damage to ensure a long service life.

Technical Informations

Item number	10003223
EAN	8903094075539
Valid tyre size	405 / 70 R 18
Alternative size 1	15.5/70R18
LI / SI / PR	153 A2 / 146 J
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 525
M+S	M+S
Carcass properties	POR,All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	66,98
Recommended rim size	13
Permitted rim size	11, 12
Maximum air pressure [bar].	4,00
Section width (mm)	405
Outer diameter of tyre [mm].	1025
Stat. radius (SLR) [mm]	462
Rolling circumference [mm].	3122
Tread depth (mm)	21,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A2	3650	10		3,75	
146 J	3000	100		4,00	