

TYRES

Product group	Tyres	
Item number	10003301	
Valid tyre size	650 / 45 - 22.5	
LI / SI / PR	173 A6 / 169 A8	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Flotation 331	





Notes and features

- The Alliance 331 is perfectly suited to on- and off-road agricultural applications e.g. for tractors, agricultural trailers and similar vehicles
- Its main characteristics are a high load capacity and low inflation pressure
- It replaces conventional tractor tyres or dual constructions because of its high traction, high load capacity and at the same time protects the soil
- Thanks to the permitted speed of 50 km/h, it can also be used on off-road trucks and trailers
- The strong nylon construction and special rubber compound make the tyre very durable



Technical Informations

Item number	10003301
EAN	7291050066938
Valid tyre size	650 / 45 - 22.5
LI / SI / PR	173 A6 / 169 A8
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 331
Carcass properties	HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	139,80
Recommended rim size	20.00DC
Maximum air pressure [bar].	4,50
Section width (mm)	645
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	535
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3567
Contact area [cm²]	1694
Tread depth (mm)	40,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	264.52
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 A6	6500	30		4,50	
169 A8	5800	40		4,50	